

## TECHNICAL DATA SHEET

Material	ISO 2076	UV Stabil Polypropylene CO / ECO Friendly / 0% PVC
Colours	EN ISO 20105-A02	No change / 19 standard colours
Size	EN 427	25,00 X 25,00 cm
Thickness	EN 428	12,2 mm
Weight	EN 430	3,22 kg/m <sup>2</sup>
Slip Resistance	CEN/TS 15676	95 USRV >0,3 DS
Squareness of tiles	HRN EN 14041	0,15 mm
Formaldehyde Emission	Class E1	No Formaldehyde emission
Content of Pentachlorophenol	-	No content
Vertical Deformation	EN 14809	0,5 mm
Resistance to Wear	EN ISO 5470-1 EN 14836	0,08 g
Friction	EN 13036-4	Dry 103 μ / Wet 55 μ
Vertical Ball Rebound	EN 12235	96 %
Shock absorption	EN 14808	12%
Heat Resistance	-	-30 - +80
Surface Protection	-	Antimicrobial Protection / KF zero growth
Water Permeability	EN 12616	27,989 mm/h / Excellent
Paint	-	Lines shall be primed and painted with 2K polyurethane as recommended by KlikFlex
Cleaning	-	Recommended for use with Husqvarna professional air blower systems. For further details please contact our customer services.
CE	HRN EN 14041 BS EN 14877	000122-000-16 AN-0407

## DELIVERY

<b>Carton Box</b>	1 BOX = 4,5 m <sup>2</sup> = 72 tiles / 1 pallet = 25 boxes = 112,50 m <sup>2</sup>	Pallet size 1,05 x 0,78 x 1,95 m / Gross weight 382,00 kg
<b>Preassembled sheets</b>	1 SHEET = 0,75 m <sup>2</sup> = 12 tiles / 1 pallet = 120 sheets = 90,00 m <sup>2</sup>	Pallet size 1,05 x 0,78 x 1,65 m / Gross weight 305,00 kg

## STORAGE

Please store material on a clean, dry, and flat surface, protected from exposure to harmful weather conditions or possible damage.



SYSTEM2**KLIK**

